



KÖSTER BD 50 Contrast

Liquid contrast agent for coloring KÖSTER BD 50

Features

Liquid contrast agent for coloring KÖSTER BD 50 before applying the second layer. Visual inspection will be simplified through color differentiation of the second waterproofing layer.

Technical Data

Color : Black

The color is filled in a small 500 ml square plastic bottle.

Fields of Application

Liquid contrast agent for coloring KÖSTER BD 50 before applying the second layer. Required for processing according to DIN 18 534-3: 2017-07, chapter 8.1. Can also be used in higher concentrations or in pure form like KÖSTER BD 50.

Application

After mixing KÖSTER BD 50 Contrast into the KÖSTER BD 50, the waterproofing material turns into a different color for the second layer application.

Consumption

approx. 100 g / 10 kg KÖSTER BD 50

Cleaning

Clean tools immediately after use with water.

Storage

Store the material cool but frost free. In originally sealed packages it can be stored for a minimum of 12 months.

Safety

Avoid eye contact. Use proper eye protection when working with the material. Observe all local, state, and federal safety guidelines when applying the material.

Related products

KÖSTER BD 50

Prod. code B 290 010

The information contained in this technical data sheet is based on the results of our research and on our practical experience in the field. All given test data are average values which have been obtained under defined conditions. The proper and thereby effective and successful application of our products is not subject to our control. The installer is responsible for the correct application under consideration of the specific conditions of the construction site and for the final results of the construction process. This may require adjustments to the recommendations given here for standard cases. Specifications made by our employees or representatives which exceed the specifications contained in this technical guideline require written confirmation. The valid standards for testing and installation, technical guidelines, and acknowledged rules of technology have to be adhered to at all times. The warranty can and is therefore only applied to the quality of our products within the scope of our terms and conditions, not however, for their effective and successful application. This guideline has been technically revised; all previous versions are invalid.

KÖSTER BAUCHEMIE AG • Dieselstraße 1-10 • D-26607 Aurich • Tel. 04941/9709-0 • Fax -40 • info@koester.eu • www.koester.eu